

Actuator for magnetic safety switch, cylindrical design M30, IP67, operating distance depending on the actuator 8/12 mm, heightdesign 13 mm, PU = 1 actuator.



Technical details

| General data | |
|---------------------------------|---|
| Approval: | CE, UKCA, cULus Listed, EAC (Eurasian), TÜV |
| unit type: | Actuator |
| Technical data | |
| Environmental data | |
| ATEX category: | II 3GD EEx nC IIC T6 |
| Ambient temperature: | -25 - 70 °C |
| Max. ambient temp. at 2000 m: | +70 °C |
| Perm. operating height ASL: | 4000 m |
| Vibration to standard ...: | EN 60947-5-2 |
| Acc. shock to standard1: | 30g |
| Pollution degree clear.&creep.: | 3 |
| Mechanical data | |
| Housing material upper part: | PBT |
| Depth dimension: | 16 mm |
| Net weight: | 20 g |
| Gross weight: | 21 g |
| Environment | |
| RoHS directive: | 2011/65/EU, 2015/863/EU |
| RoHS conformity: | yes |

| | |
|--------------------------------|------------------------------|
| RoHS exceptions: | no |
| REACH compliance: | Contains no SVHC substances |
| WEEE classification (08/2018): | 5 devices (feed size < 50cm) |
| Commercial data | |
| Harmonized System Code: | 85389099 |
| UNSPSC 25: | 39122205 |
| EAN-Code: | 4046548003376 |
| ECLASS version: | ECLASS-13 |
| ECLASS Reference Feature: | 27274002 |
| ETIM Version: | ETIM-9.0 |
| ETIM Reference Group: | EG000026 |
| ETIM Reference Feature: | EC001487 |
| Volume: | 0 dm3 |